



The  
**PlasticPeople**®

## Magnetic Glazing Fitting Instructions

**This magnetic tape is intended for internal use and should not be used with glass.**

**When using with an opening window, always fit to the main window frame and not the opening section.**

### Measuring Your Windows

When measuring your windows for secondary glazing you need to make sure that the plastic will overlap the frame by at least the thickness of the magnetic tape. To do this you should measure the window vertically and horizontally (not including the frame) and add on at least 25mm to each measurement.

If you can leave a bit more room either side, even better. It will make removing the secondary glazing that much easier.

**Note:** when installing the secondary glazing make sure there is a flat mounting surface of at least 20mm around each side of the window glazing.

### Sheet Size Guidance

2mm sheet - panels under 4000mm perimeter

3mm sheet - panels between 4000mm and 4500mm

### Tools Required

Tape Measure, pencil and sturdy pair of scissors.

### Fitting Guide

- Cut and stick the black magnetic tape to the edges of the secondary glazing panel.
- Hold the secondary glazing panel to the window frame so that it overlaps equally on all sides.
- Draw a pencil line around the sheet on the frame.
- Cut and stick the white metal strip to the window frame, using the pencil marks as a guide.
- You can now hold the secondary glazing panel up to the window and CLICK it into place.

**CAUTION:** *care must be taken when handling the steel strip as the edges can be sharp and can cause 'paper cut' style injuries if not handled with care.*

For larger windows, we recommend using clips and screws for extra support to stop the secondary glazing panel from slipping.